

SI Stangkop GIR12-UK-DURBAL - GIR12-UK-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gir12-uk-durbal>

GIR12-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number right hand thread left hand thread	measurement [mm]							
	d	G	B	C ₁	C ₂	d ₂	d ₄	
GIR 12 UK	12	M12	10	8,0	34	17,5	22	
type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]		
GIR / GRL 12 UK	t ₃ min	h	W				24,5	0,096

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493695
Binnendiameter	12 mm
Buitendiameter	34 mm
Dikte	10 mm
Type	SI
Gewicht	96 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE