

SI Stangkop GIR15-UK-DURBAL - GIR15-UK-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gir15-uk-durbal>

GIR15-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	d ₂	d ₄
GIR 15 UK	15	M 14	12	10,0	40	21,0 26

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 15 UK	30	61	22	8	36,0	0,180

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493725
Binnendiameter	15 mm
Binnendiameter	0.591" inch
Buitendiameter	40 mm
Buitendiameter	1.575" inch
Dikte	12 mm
Dikte	0.472" inch
Type	SI
Gewicht	180 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE