

# SI Stangkop GIR25-UK-2RS-DURBAL - GIR25-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gir25-uk-2rs-durbal>

## GIR25-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	measurement [mm]	
GIR 25 UK (-2RS)	d	G
	25	M 24 x 2
	B	20
	C <sub>1</sub>	17,0
	C <sub>2</sub>	64
	d <sub>2</sub>	33,5
	d <sub>4</sub>	42

  

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	h	W			
GIR / GRL 25 UK	48	94	36	7	83,0	0,640

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952493961
Binnendiameter	25 mm
Buitendiameter	64 mm
Dikte	20 mm
Type	SI
Gewicht	640 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE