

SI Stangkop GIL60-UK-2RS-DURBAL - GIL60-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gil60-uk-2rs-durbal>

GIL60-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	C ₁	C ₂	d ₂	d ₄
GIL 60 UK-2RS	60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 60 UK-2RS	70	175	75	6	450,0	5,500

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494258
Binnendiameter	60 mm
Binnendiameter	2.362" inch
Buitendiameter	135 mm
Buitendiameter	5.315" inch
Dikte	44 mm
Dikte	1.732" inch
Type	SI
Gewicht	5500 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE