

# SI Stangkop GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gir70-uk-2rs-durbal>

## GIR70-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free

order number	measurement [mm]	
GIR 70 UK-2RS	d 70	G M 56 x 4
	B 49	C <sub>1</sub> 42,0
	d <sub>2</sub> 160	d <sub>3</sub> 80,0
	d <sub>4</sub> 98	

  

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIL 70 UK-2RS	80	200	85	6	610,0	8,600

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494296
Binnendiameter	70 mm
Buitendiameter	160 mm
Dikte	49 mm
Type	SI
Gewicht	8600 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE