

SI Stangkop GIR80-UK-2RS-DURBAL - GIR80-UK-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/gir80-uk-2rs-durbal>

GIR80-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
			d	G	B	C ₁	C ₂	d ₂	d ₃	d ₄
GIR 80 UK-2RS			80	M 64 x 4	55	47,0	180	95,0	110	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 80 UK-2RS	85	230	100	6	750,0	12,000

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952494326
Binnendiameter	80 mm
Buitendiameter	180 mm
Dikte	55 mm
Type	SI
Gewicht	12000 g
Draad	Rechtse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE