

SI Stangkop SIZP19-S-DURBAL - SIZP19-S-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sizp19-s-durbal>

SIZP19-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

| order number | measurement [mm] | | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|----------|-------|-------|-------|-------|-------|
| | right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
| SIZP 19 S | | | 19,05 | 3/4 - 16 | 22,23 | 17,45 | 44,45 | 25,02 | 28,58 |

| type | inches | measurement [mm] | | | alpha [°] | load rating C ₀ [kN] | weight [kg] |
|-------------------|---------|--------------------|-------|-------|-----------|---------------------------------|-------------|
| | | l ₁ min | W | h | | | |
| SIZP / SIZPL 19 S | 3 / 4 " | 44,45 | 25,40 | 73,03 | 10 | 29,0 | 0,285 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952495910 |
| Binnendiameter | 19.05 mm |
| Buitendiameter | 44.45 mm |
| Dikte | 22.23 mm |
| Type | SI |
| Gewicht | 285 g |
| Draad | Rechtse draad |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE