

SA Stangkop DSAZPL4-S-DURBAL - DSAZPL4-S-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/dsazpl4-s-durbal>


DSAZPL4-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number	measurement [mm]		C ₁	d ₂
	right hand thread	left hand thread		
DSAZPL 4 S	4,83	10 - 32	7,92	6,35

type	inches	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
		l ₁ min	h			
DSAZP / DSAZPL 4 S		19,05	31,75	10	3,8	0,013

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952496009
Binnendiameter	4.83 mm
Buitendiameter	15.88 mm
Dikte	7.92 mm
Type	SA
Gewicht	13 g
Draad	Linkse draad
Smering	zonder
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE