

GE Stangkop

SIL6-E-DURBAL - SIL6-E-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/sil6-e-durbal>


SIL6-E



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		right hand thread		left hand thread		measurement (mm)					
SIL 6 E		d	G	B	C1	d2	d3	d4			
SIL 6 E		6	M 6	6	4,4	21	10,0	13			

type	measurement (mm)			α [°]	load rating C_0 [kN]	weight [kg]
	l_2 min	W	h			
SI / SIL 6 E	11	11	30	13	8,2	0,021

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060467881
Binnendiameter	6 mm
Buitendiameter	21 mm
Dikte	6 mm
Type	GE
Gewicht	21 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE