

SI Stangkop SIL20-ES-DURBAL - SIL20-ES-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil20-es-durbal>

SIL20-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)					
SIL 20 ES		d	G	B	C ₁	d ₂	d ₄
		20	M 20 x 1,5	16	13,0	53	27,5

measurement [mm]

type	l ₁ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SI / SIL 20 ES	40	32	77	9	60,0	0,35

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497068
Binnendiameter	20 mm
Buitendiameter	53 mm
Dikte	16 mm
Type	SI
Gewicht	350 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE