

SI Stangkop

SIL30-ES-2RS-DURBAL - SIL30-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil30-es-2rs-durbal>

SIL30-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number	right hand thread	left hand thread	measurement (mm)						
SIL 30 ES (-2RS)			d	G	B	C1	d2	d3	d4
			30	M 30 x 2	22	19,0	73	40,0	50

type	l ₁ min	measurement [mm]			load rating	weight
		W	h	α [°]	C ₀ [kN]	[kg]
SI / SIL 30 ES (-2RS)	56	41	110	6	110,0	0,93

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497273
Binnendiameter	30 mm
Binnendiameter	1.181" inch
Buitendiameter	73 mm
Buitendiameter	2.874" inch
Dikte	22 mm
Dikte	0.866" inch
Type	SI
Gewicht	930 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE