

# SI Stangkop

## SIL35-ES-2RS-DURBAL - SIL35-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil35-es-2rs-durbal>

### SIL35-ES-2RS



**female thread;**  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DS1...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 35 ES (-2RS)		35	M 36 x 3

type	measurement [mm]			load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h		
SI / SIL 35 ES (-2RS)	60	50	125	146,0	1,3

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497303
Binnendiameter	35 mm
Buitendiameter	82 mm
Dikte	25 mm
Type	SI
Gewicht	1300 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE