

SI Stangkop SIL35-ES-DURBAL - SIL35-ES-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil35-es-durbal>

SIL35-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
	SIL 35 ES	35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]				load rating C_0 [kN]	weight [kg]
	l_1 min	W	h	α [°]		
SI / SIL 35 ES	60	50	125	6	146,0	1,3

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497310
Binnendiameter	35 mm
Binnendiameter	1.378" inch
Buitendiameter	82 mm
Buitendiameter	3.228" inch
Dikte	25 mm
Dikte	0.984" inch
Type	SI
Gewicht	1300 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE