

SI Stangkop

SIL40-ES-2RS-DURBAL - SIL40-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil40-es-2rs-durbal>

SIL40-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

Rod end body: surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 40 ES (-2RS)		40	M 39 x 3

type	measurement [mm]			load rating C_0 [kN]	weight [kg]
	l_1 min	W	h		
SI / SIL 40 ES (-2RS)	65	55	142	180,0	2,0

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497433
Binnendiameter	40 mm
Binnendiameter	1.575" inch
Buitendiameter	92 mm
Buitendiameter	3.622" inch
Dikte	28 mm
Dikte	1.102" inch
Type	SI
Gewicht	2000 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE