

# SI Stangkop

## SIL60-ES-2RS-DURBAL - SIL60-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/sil60-es-2rs-durbal>

### SIL60-ES-2RS



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**Rod end body:** surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 60 ES (-2RS)		60	M 52 x 3

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SIL 60 ES (-2RS)	70	75	175	6	450,0	5,5

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497624
Binnendiameter	60 mm
Binnendiameter	2.362" inch
Buitendiameter	135 mm
Buitendiameter	5.315" inch
Dikte	44 mm
Dikte	1.732" inch
Type	SI
Gewicht	5500 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE