

SI Stangkop SI60-ES-DURBAL - SI60-ES-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/si60-es-durbal>

SI60-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SI 60 ES		60	M 52 x 3

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SII 60 ES	70	75	175	6	450,0	5,5

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497662
Binnendiameter	60 mm
Buitendiameter	135 mm
Dikte	44 mm
Type	SI
Gewicht	5500 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE