

# SI Stangkop

## SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/si60-es-2rs-durbal>

### SI60-ES-2RS



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread
SI 60 ES (-2RS)	

**measurement (mm)**

d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
60	M 52 x 3	44	38,0	135	70,0	88

**measurement [mm]**

type	l <sub>3</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SI / SII 60 ES (-2RS)	70	75	175	6	450,0	5,5

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497679
Binnendiameter	60 mm
Buitendiameter	135 mm
Dikte	44 mm
Type	-
Gewicht	5500 g
Draad	-
Smering	-
Verpakking	-
Standaard	-

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE