

SI Stangkop SI80-ES-DURBAL - SI80-ES-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/si80-es-durbal>

SI80-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 80 ES	d	G	B	C ₁	measurement (mm)		
					d ₂	d ₃	d ₄
	80	M 64 x 4	55	47,0	180	95,0	110

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497792
Binnendiameter	80 mm
Buitendiameter	180 mm
Dikte	55 mm
Type	SI
Gewicht	12000 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE