

SA Stangkop SAL10-E-DURBAL - SAL10-E-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/sal10-e-durbal>

SAL10-E



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 10 E	10	M 10	9	7,0	29	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 10 E	26	15	48	12	17,6	0,051	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952497952
Binnendiameter	10 mm
Binnendiameter	0.394" inch
Buitendiameter	29 mm
Buitendiameter	1.142" inch
Dikte	9 mm
Dikte	0.354" inch
Type	SA
Gewicht	51 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE