

SA Stangkop

SA15-ES-2RS-DURBAL - SA15-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/sa15-es-2rs-durbal>

SA15-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 15 ES (-2RS)		15	M 14	12	10,0	40

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SA 15 ES (-2RS)	34	20	63	8	36,0	0,140

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498034
Binnendiameter	15 mm
Buitendiameter	40 mm
Dikte	12 mm
Type	-
Gewicht	140 g
Draad	-
Smering	-
Verpakking	-
Standaard	-

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE