

SA Stangkop SA25-ES-DURBAL - DSA25-ES-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/dsa25-es-durbal>

SA25-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 25 ES		25	M 24 x 2	20	17,0	64

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 25 ES	53	32	94	7	83,0	0,560

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498317
Binnendiameter	25 mm
Buitendiameter	64 mm
Dikte	20 mm
Type	SA
Gewicht	560 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE