

SA Stangkop

SA35-ES-2RS-DURBAL - SA35-ES-2RS-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/sa35-es-2rs-durbal>

SA35-ES-2RS



male thread:
lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 35 ES (-2RS)		35	M 36 x 3	25	21,0	82

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 35 ES (-2RS)	82	41	140	6	146,0	1,400

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952498478
Binnendiameter	35 mm
Buitendiameter	82 mm
Dikte	25 mm
Type	SA
Gewicht	1400 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE