

TAPR Stangkop GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/tapr/giho-k-16do-durbal>

GIHO-K-16DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-K 16 DO*		16	20,7	45	M 12 x 1,25	21	45	14	11	13	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952500652
Binnendiameter	16 mm
Buitendiameter	45 mm
Dikte	11 mm
Type	TAPR
Gewicht	220 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE