

GE Stangkop

BRTM12-01-502-DURBAL - BRTM12-01-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/brtm12-01-502-durbal>

BRTM12-01-502



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

liner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]							
type	type hard thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂
BRTM 12 -01	-502		12	M 12		14,5	32	16	12
		measurements [mm]			weight	rotational speed limit	basic load rating		
type	h	l	b ₃	α [°]	[kg]	n _{max} [min ⁻¹]	C [N]	stat. C ₀ [N]	
BRTM 12	54	33	19	7,5	0,088	1125	10250	6600	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060468161
Binnendiameter	12 mm
Buitendiameter	32 mm
Dikte	16 mm
Type	GE
Gewicht	88 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE