

GE Stangkop BRTM30-00-501-DURBAL - BRTM30-00-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/brtm30-00-501-durbal>

BRTM30-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]								
type	type hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃
BRTM 30 -00	-501		30	M 30 x 2		34,5	70		37	25
measurements [mm]		weight		rotational speed limit		basic load rating		dyn.		stat.
type	h	l	b ₃	α	[°]	[kg]	n _{max}	C	C ₁₀	C ₉₀
BRTM 30	110	66	35	7,5		0,912	450	32500	24850	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3616060468178
Binnendiameter	30 mm
Buitendiameter	70 mm
Dikte	37 mm
Type	GE
Gewicht	912 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE