

SI Stangkop

BRTF16-03-501-DURBAL - BRTF16-03-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/brtf16-03-501-durbal>

BRTF16-03-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number			measurements [mm]																				
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₆	d ₇	h ₁	b ₂	h	l	l ₁	l ₂	l ₃	SW	α	weight	rotational speed limit	basic load rating	stat. C	stat. C ₀	
BRTF 16 -03	-501		16	22,0	M 16	19,0	42	27	21	15													
type	h	l	l ₁	l ₂	l ₃	SW	α	weight	rotational speed limit	basic load rating	stat. C	stat. C ₀											
BRTF 16	64	28	8,0	22	22	7,0		0,220	975	13300	8900												

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952506852
Binnendiameter	16 mm
Buitendiameter	42 mm
Dikte	21 mm
Type	SI
Gewicht	220 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE