

# SI Stangkop

## BRF10-00-501-DURBAL - BRF10-00-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/brf10-00-501-durbal>

### BRF10-00-501



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

**inner ring:**  
ball bearing steel, hardened, superfinished.

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10)  
DIN 71 412 H1 (sizes 12 to 30)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	right-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h	
BRF 10 -00 -501		10	15,0	M 10	12,0	28	19	14	10,5	43		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating				
type	l	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	β [g]	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C [N]	C <sub>0</sub> [N]	
BRF 10	20	6,5	15	17	8,0	0,072	1,90	1,81	1225	4450	1450	

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507187
Binnendiameter	10 mm
Buitendiameter	28 mm
Dikte	14 mm
Type	SI
Gewicht	72 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE