

SI Stangkop

PF10-00-502-DURBAL - PF10-00-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/pf10-00-502-durbal>

PF10-00-502



rod end housing:
forged steel, case-hardened bearing race,
superfinished, surface galvanized,
free of Cr VI

inner ring:
ball bearing steel, hardened,
superfinished


lubrication:
aluminium-complex soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing



female thread;
long-term
lubrication,
low maintenance,
shields



order number		measurements (mm)									
type	right hand thread left hand thread	d1	d2	d3	d4	d5	d6	b1	b2		
PF 10 -00	-502	10	15	M 8	13,0	30	13,0	13,0	9		
		measurements (mm)									
type		h	l	l3	r	SW	α	weight	calculation factors	rotational speed limit	basic load rating
PF 10		38	17	14,5	10	13	7,0	0,063	1,90 1,81	1225	2605 985

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507378
Binnendiameter	10 mm
Buitendiameter	30 mm
Dikte	13 mm
Type	SI
Gewicht	63 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE