

SI Stangkop

PF15-00-502-DURBAL - PF15-00-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/pf15-00-502-durbal>

PF15-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields

| order number | | measurements (mm) | | | | | | | | | | |
|-------------------|-------------------|-------------------|---------------------|------------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|------|
| type | right hand thread | left hand thread | d ₁ | d ₂ | d ₃ | d ₄ | d ₅ | d ₆ | b ₁ | b ₂ | | |
| PF 15 -00 | -502 | | 15 | 19 | M 12 | 17,5 | 40 | 16,5 | 12 | | | |
| measurements (mm) | | weight | calculation factors | rotational speed limit | basic load rating | | | | | | | |
| type | h | l | l ₁ | r | SW | α | Y | Y ₀ | lim (min) | C | C ₀ | |
| PF 15 | 51 | 24 | 20,0 | 15 | 17 | 7,0 | 0,140 | 2,30 | 2,41 | 1025 | 5000 | 1890 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DURBAL |
| N° Ean13 | 3663952507385 |
| Binnendiameter | 15 mm |
| Buitendiameter | 40 mm |
| Dikte | 16.5 mm |
| Type | SI |
| Gewicht | 140 g |
| Draad | Linkse draad |
| Smering | met |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE