

# SI Stangkop

## PF20-00-502-DURBAL - PF20-00-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/pf20-00-502-durbal>

### PF20-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3485 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread;**  
long-term lubrication, low maintenance, shields

order number		measurements (mm)										
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>		
PF 20 -00	-502		20	22	M 16	24,0	48	20,5	15			
measurements (mm)		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	r	SW	α	Y	Y <sub>0</sub>	n <sub>max</sub> (min <sup>-1</sup> )	C <sub>dyn</sub> (N)	C <sub>stat</sub> (N)		
PF 20	65	32	22,0	20	19	6,5	0,223	2,34	2,45	850	6105	2955

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507415
Binnendiameter	20 mm
Buitendiameter	48 mm
Dikte	20.5 mm
Type	SI
Gewicht	223 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE