

SA Stangkop PM06-00-502-DURBAL - PM06-00-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/pm06-00-502-durbal>


PM06-00-502



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀ [N]
PM 06 -00	-502	6	M 10 x 1		8,5	24	14	14	10						
type		l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	Y	Y ₀	n _{max} [min ⁻¹]	C <td>C₀ [N]</td>	C ₀ [N]
PM 06		42,5	17	64	1,5	2,5	10,5			0,062	1,28	1,34	1300	2445	765

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507477
Binnendiameter	6 mm
Buitendiameter	24 mm
Dikte	14 mm
Type	SA
Gewicht	62 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE