

SA Stangkop PM10-00-501-DURBAL - PM10-00-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/pm10-00-501-durbal>

PM10-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]	
type	type	d ₁	d ₂
PM 10 -00	-501	10	M 14 x 1,5
		d ₃	d ₄
		13,5	36
		d ₅	d ₇
		19	20
		b ₁	b ₂
		14	14

measurements [mm]		weight [kg]	calculation factors Y %	rotational speed limit n _{max} [min ⁻¹]	basic load rating C [N]	
type	type				C	C ₀
PM 10	49,5 28 82 2,5 2,5 9,5	0,168	1,69 1,77	1100	5120	1905

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507545
Binnendiameter	10 mm
Buitendiameter	36 mm
Dikte	20 mm
Type	SA
Gewicht	168 g
Draad	Rechtse draad
Smering	met
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE