

# SA Stangkop

## PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/pm15-00-501-durbal>

### PM15-00-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISOA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating				
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C [N]	C <sub>0</sub> [N]		
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14						
measurements [mm]		weight		rotational speed limit		basic load rating								
type	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	u	z	α [°]	weight [kg]	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C [N]	C <sub>0</sub> [N]
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17	975	5485	3270		

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507620
Binnendiameter	15 mm
Buitendiameter	42 mm
Dikte	20 mm
Type	SA
Gewicht	310 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE