

# SA Stangkop PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/pm15-02-501-durbal>


## PM15-02-501



male thread:  
long-term  
lubrication,  
low maintenance,  
shields



**DURBAL® heavy-duty rod ends  
with integral self-aligning  
ball bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminium-complex-soap-grease,  
temperature range: -45 °C to +120 °C,  
approval according to USGA H1

lubrication fitting:  
DIN 3405 D1/A

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C	C <sub>0</sub> [N]
PM 15 -02 -501	15	M 20 x 1.5	18.5	42	26	20	14								
measurements [mm]		weight		rotational speed limit		basic load rating									
type	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	u	z	α [°]	weight [kg]	calculation factors	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C	C <sub>0</sub> [N]
PM 15	36	30	73.5	3.0	2.5	6.5	0.273		2.07	2.17			975	5485	3270

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507651
Binnendiameter	15 mm
Buitendiameter	42 mm
Dikte	20 mm
Type	SA
Gewicht	273 g
Draad	Rechtse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE