

SA Stangkop PM20-00-501-DURBAL - PM20-00-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/pm20-00-501-durbal>


PM20-00-501



male thread:
long-term
lubrication,
low maintenance,
shields



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		measurements [mm]		measurements [mm]		measurements [mm]		measurements [mm]		
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	l ₁	l ₂	l ₃	
PM 20 -00	-501	20	M 24 x 1.5	24,0	56	30	24	18						
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	calculation factors Y	calculation factors Y ₀	rotational speed limit [min ⁻¹]	basic load rating C [N]	stat. load rating C ₀ [N]
PM 20	68,5	41	117	3,5	3,0	5,5			0,587	2,76	2,90	775	6165	3140

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952507705
Binnendiameter	20 mm
Binnendiameter	0.787" inch
Buitendiameter	56 mm
Buitendiameter	2.205" inch
Dikte	24 mm
Dikte	0.945" inch
Type	SA
Gewicht	587 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE