

SA Stangkop

BRM06-60-502-DURBAL - BRM06-60-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/brm06-60-502-durbal>

BRM06-60-502



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 2402 D1/L6 (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]							
type	left-hand thread	d ₁	d ₂						
BRM 06 -60	-502	6	M 6						
		d ₄	d ₅						
		9,0	20						
		l ₁	l ₂						
		6,75	36						
measurements [mm]		weight	calculation-factors	rotational speed limit	basic load rating				
type	l	α [°]	Y	lim. [min ⁻¹]	C _d [N]				
BRM 06	22	12	8,0	0,019	2,09	2,19	1350	1900	450

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952509099
Binnendiameter	6 mm
Buitendiameter	20 mm
Dikte	9 mm
Type	SA
Gewicht	19 g
Draad	Linkse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE