

# SA Stangkop

## BRM20-60-502-DURBAL - BRM20-60-502-DURBAL

https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/brm20-60-502-durbal

### BRM20-60-502



**male thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel**

**rod end housing:**  
stainless steel 1.4024, hardened, bearing race superfinished, rolled thread

**inner ring:**  
stainless steel, hardened, surface superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 2402 DTuk (sizes 6 to 10) DIN 71 412 H1 (sizes 12 to 20)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number	male thread	measurements [mm]						
type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	d <sub>5</sub>	l <sub>1</sub>	l <sub>2</sub>	h
BRM 20 -60	-502	20	M 20 x 1,5	24,5	50	25	18,0	78
			weight	calculation factors	rotational speed limit	basic load rating		
type	measurements [mm]	α [°]	[kg]	Y	v <sub>0</sub>	C	C <sub>0</sub>	C <sub>10</sub>
BRM 20	l l <sub>2</sub>					[min]	[N]	[N]
	47 28	7,0	0,338	2,46	2,58	825	5350	2300

## PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952509181
Binnendiameter	20 mm
Buitendiameter	50 mm
Dikte	25 mm
Type	SA
Gewicht	338 g
Draad	Linkse draad
Smering	met
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE