

SI Stangkop

BRF20-60-501-DURBAL - BRF20-60-501-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/brf20-60-501-durbal>

BRF20-60-501



rod end housing:
stainless steel 1.4534, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminum-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	light load thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h	
BRF 20 -60	-501	20	27,5	M 20 x 1,5	24,5	50	34	25	18,0	77		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.		
type	l	l ₁	l ₂	SW	α [°]	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	C ₁₀	
BRF 20	33	10,0	26	30	7,0	0,367	2,46	2,58	825	5350	2300	

PRODUCTKENMERKEN

Merk	DURBAL
N° Ean13	3663952509310
Binnendiameter	20 mm
Buitendiameter	50 mm
Dikte	25 mm
Type	SI
Gewicht	367 g
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE