

## SI Stangkop

### BEF06-60-502-DURBAL - BEF06-60-502-DURBAL

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/bef06-60-502-durbal>

#### BEF06-60-502



rod end heading:  
stainless steel 1.4301, rolled thread,  
surface with pickling treatment


joint ball:  
stainless steel, hardened and ground,  
surface superfinished

race:  
nylon / teflon / glass fibre compound

tolerances:  
see page 10

**DURBAL® heavy-duty rod ends  
with integral spherical  
plain bearing in stainless steel**

female thread:  
maintenance free,  
adapter sizes  
according to  
DIN ISO 12240-4,  
series K,  
thread according to  
ISO 8139



| order number      |                   | measurements [mm] |                |                |                |                |                    |                    |                |                |                |                             |                |
|-------------------|-------------------|-------------------|----------------|----------------|----------------|----------------|--------------------|--------------------|----------------|----------------|----------------|-----------------------------|----------------|
| type              | right hand thread | left hand thread  | d <sub>1</sub> | d <sub>2</sub> | d <sub>3</sub> | d <sub>4</sub> | d <sub>5</sub>     | d <sub>6</sub>     | d <sub>7</sub> | d <sub>8</sub> | b <sub>1</sub> | b <sub>2</sub>              | b <sub>3</sub> |
| BEF 06            | -60               | -502              | 6              | 10,0           | M 6            | 20             | 13                 | 12,65              | 9              | 6,75           |                |                             |                |
| measurements [mm] |                   | weight            |                |                |                |                |                    |                    |                |                |                |                             |                |
| type              | h                 | l                 | l <sub>1</sub> | l <sub>2</sub> | l <sub>3</sub> | SW             | α <sub>1</sub> [°] | α <sub>2</sub> [°] | β [°]          | C              | C <sub>0</sub> | basic load rating stat. [N] |                |
| BEF 06            | 30                | 12                | 5,0            | 10             | 11             | 13,0           | 6,5                | 0,024              | 2820           | 8500           |                |                             |                |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | DURBAL        |
| N° Ean13       | 3663952509372 |
| Binnendiameter | 6 mm          |
| Buitendiameter | 20 mm         |
| Dikte          | 9 mm          |
| Type           | SI            |
| Gewicht        | 24 g          |
| Draad          | Linkse draad  |
| Smering        | zonder        |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE