


Vrijloop FCBN-4-K-NADELLA - FCBN-4-K-NADELLA

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/vrijloop/fcbn-4-k-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page.
Types FCBL and FCBL clutch and bearing assemblies have stainless steel springs inserted in the molded cage to position rollers for instantaneous lockup.



Shaft Ø mm	Designation	F _e mm	D mm	C mm	Torque Nm	Load ratings 1)		Overrun limiting speed rating for rotating shaft min ⁻¹
						Dynamic C _d kN	Static C _s kN	
4	FCBN-4-K	4	10	9	0.19	1.86	0.99	26000

Shaft Ø mm	Gagging				Z Minimum outer diameter of steel housing for Torque mm	Mounting				Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun and bearing go plug mm	Bearing no go plug mm		S - Shaft raceway diameter		H - Housing bore		
						Max. mm	Min. mm	Max. mm	Min. mm	
4	9.984	3.980	4.004	4.030	16	4.000	3.995	9.983	9.984	0.003

PRODUCTKENMERKEN

Merk	NADELLA
N° Ean13	3663952529516
Binnendiameter	4 mm
Buitendiameter	10 mm
Dikte	9 mm
Gewicht	3 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE