




Naaldhulslager TJ7214-RBC - TJ7214-RBC

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/tj7214-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fillet	Housing Shoulder Dia	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Max.	Min.	+0.00 -0.00	Max	±.184"		
TJ 7214	1.18	1.1259	1.1208	1.3250	1.3240	1.000	.040	1.38	8,500	15,500

Limit Speed (rpm)	Recommended Shaft Diameter				Recommended Housing Bore				BEARING PART NUMBER 1)		
	ISO H6 use with H7 sig fit		ISO H6 use with H7 sig fit		Slip Fit ISO H7		Press Fit ISO N7				
	Max.	Min.	Max.	Min.	Min.	Max.	Mean Fit	Min.		Max.	Mean Fit
10,500	1.1290	1.1245	1.1242	1.1227	1.6250	1.6280	.0007L	1.6237	1.6247	.0006T	TJ 7214

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

PRODUCTKENMERKEN

Merk	RBC
N° Ean13	3663952533490
Binnendiameter	28.575 mm
Buitendiameter	41.275 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE