



# SA Stangkop MPL-07-F-DUNLOP - MPL-07-F-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/mpl-07-f-dunlop>

MALE ROD ENDS 



**MP-SERIES: MP - MPS - MP 55**

**Description**  
MP-Series is our 3-piece standard range of self-lubricating general purpose male rod ends suitable for light to medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. They have excellent moisture resistance and require no maintenance and have a wide operating temperature range.

**Material Specifications**  
Housing: Steel 230M07PB and forged 080M46, zinc plated and clear trivalent plastic and stainless steel 303L & 304 forged. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C and 52100. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

**Features**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating  
Good wear resistance  
Excellent moisture resistance  
Studded option

**Possible Applications**  
Light to medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
Precision equipment  
No maintenance  
Linear movement

**Temperature Range**  
-30°C to +170°C

**Specification**  
ELV & RoHS compliant

Housing: Steel 230M07PB (Sizes 05 - 07)  
Forged 080M46 (Sizes 09 - 14)  
Zinc Plated and Clear Trivalent Passivate

Race: GR-Nylon LV-3H

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MPL-07F	7/16	7/16 B5F	0.542 0.637	1.125	2.125	1.375	0.586			19.750

**Interchange table**

Dunlop	Rose	Tuthill	Alinabal	SKF	Asahi	IKO
MP-M (metric)	MMMP	MJ-M	MFM-M	SAKB-M	JAM EC	POS-EC
MP (imperial)	BMMP	MJ	PM-	-	-	POSB-EC

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add '55' to part no. For example 'MP-M03 55'

## PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3663952556130
Binnendiameter	11.113 mm
Buitendiameter	28.575 mm
Dikte	11.1 mm
Type	SA
Draad	Linkse draad
Smering	zonder
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE