


## Andere MH-12-F-DUNLOP - MH-12-F-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/andere/mh-12-f-dunlop>

**MALE ROD ENDS** **DUNLOP**



**MH SERIES: MH - MHS - MH SS**

**Description:**  
MH series is our 3-piece unique internationally patented range of male rod ends incorporating a polyurethane bearing race that provides ultra smooth operation. A nitroce surface protected ball with a PTFE lubricant provide superior shock load and extended wear properties, combined with excellent chemical and corrosion resistance. The unique innovative captive body design prevents detachment through excessive axial loads. For optimum performance, ensure that the rod end is mounted with the moulded lettering facing away from the direction of pull.

**Material Specifications:**  
Housing: Steel 230M07PB zinc plated and clear trivalent passivate. Race: Polyurethane. Ball: 230M07PB nitroce finish. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303C. Lubricant: UniLor Oil.

**Features:**  
Metric & imperial sizes  
Ultra low friction  
High shock loads  
Extended wear life  
No maintenance  
Shielded option

**Possible Applications:**  
Light to medium  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control  
Safety features

**Temperature Range:**  
-40°C to + 80°C

**Specifications:**  
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MH-12F		3/4	3/4 BSF	0.875	0.689	1.75	2.875	1.75	0.978	92,000

### PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3663952556765
Binnendiameter	19.05 mm
Buitendiameter	44.45 mm
Dikte	17.501 mm
2e Dikte	22.225 mm
Type	SA
Draad	Rechtse draad
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE