

Kogellager enkele rij 1604-SS-NICE - 1604-SS-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/1604-ss-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|-------------------|------------------|-------------------------------|-------------------------------|------------------------------------|------------------------------------|--------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 1604™ | | | | | SS | +0.000 +0.000 -0.005 -0.013 | +0.000 +0.000 -0.005 -0.013 |
| | | | | | | 0.3750 9.525 | 0.8750 22.225 |
| WIDTH | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
| B (in) (mm) | C (lb) (N) | C ₀ (lb) (N) | W ^⓪ (lb) (g) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.2813 7.150 | 644 2866 | 255 1135 | 0.03 0.01 | 0.474 12.04 | 0.778 19.78 | 0.015 0.38 | |

^⓪ Width for sealed versions = 0.3438 (8.733) ^⓪ Weights given are for greased and sealed versions

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | NICE |
| N° Ean13 | 3663952557052 |
| Binnendiameter | 9.525 mm |
| Buitendiameter | 22.225 mm |
| Dikte | 7.15 mm |
| Gewicht | 10 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE