

Kogellager enkele rij 3007-SC-NICE - 3007-SC-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/3007-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3007™ | | | SC | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.015 0.0003 |
| | | | | | | 0.4375 11.113 | 0.9063 23.020 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|------------------------------|-------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | W (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.3125 7.938 | 350 1568 | 300 1355 | 0.03 0.01 | 0.517 13.13 | 0.778 19.76 | 0.015 0.38 |

Ⓞ Weights given are for greased and sealed versions
Ⓞ 3038 and larger +.0000/-0.005 (-.000/-0.15)

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | NICE |
| N° Ean13 | 3663952558264 |
| Binnendiameter | 11.113 mm |
| Buitendiameter | 23.02 mm |
| Dikte | 7.938 mm |
| Gewicht | 10 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE