

Kogellager enkele rij 3028-SC-NICE - 3028-SC-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/3028-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|-------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3028™ | | SC | | | | +0.005 +0.13 -0.000 -0.005 | +0.000 +0.00 -0.013 -0.005 |
| | | | | | | 0.8450 15.875 | 1.5250 41.275 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|-----------------------------|--------------------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC Ca (lb) (N) | W ^⓪ (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.5000 12.700 | 1300 5795 | 1010 4489 | 0.18 0.08 | 0.845 21.46 | 1.446 36.73 | 0.025 0.64 |

^⓪ Weights given are for greased and sealed versions
[Ⓢ] 3028 and larger +0.0005/-0.005 (+0.001/-0.13)

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | NICE |
| N° Ean13 | 3663952558639 |
| Binnendiameter | 15.875 mm |
| Buitendiameter | 41.275 mm |
| Dikte | 12.7 mm |
| Gewicht | 80 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE