

## Kogellager enkele rij 3033-SC-NICE - 3033-SC-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/3033-sc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.00 -0.005	O.D. D (in) (mm) +0.000 +0.00 -0.005
3033™		SC				0.8250 15.875	1.7000 44.450

WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	BASIC LOAD RATINGS		WEIGHT W (lb) (kg) 0.22 0.10	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N) 1300 5785	STATIC C <sub>0</sub> (lb) (N) 1025 4561		d <sub>a</sub> min (in) (mm) 0.845 21.46	D <sub>a</sub> max (in) (mm) 1.530 38.86	r max (in) (mm) 0.025 0.84
0.5000 12.700	1300 5785	1025 4561	0.22 0.10	0.845 21.46	1.530 38.86	0.025 0.84

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3038 and larger +0.0005/-0.005 (+0.001/-0.13)

### PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952558738
Binnendiameter	15.875 mm
Buitendiameter	44.45 mm
Dikte	12.7 mm
Gewicht	100 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE