

## Kogellager enkele rij 3035-DS-NICE - 3035-DS-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/3035-ds-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3035™			DS			+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.0005
						2.7500 19.050	1.7500 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1025 4561	0.20 0.09	0.965 24.51	1.530 38.99	0.025 0.64

0 Weights given are for greased and sealed versions  
1 3035 and larger +0.0005/-0.0005 (+0.001/-0.12)

### PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952558776
Binnendiameter	19.05 mm
Buitendiameter	44.45 mm
Dikte	12.7 mm
Gewicht	90 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE