

# Kogellager enkele rij 7514-DL-NICE - 7514-DL-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/7514-dl-nice>

**7500 Series™ Heavy Duty Precision Ground Radial Bearings** NICE

- PRECISION GRINDING ON ALL CONTACT SURFACES TO THE 100 MICROMETER STANDARD
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 10000 RPM
- THROUGH HARDENED BEARING STEEL
- REFINED FINISH
- WIDER RETAINER STANDARDS
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE CONTACT ROLL WITH TIGHT TOLERANCES
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS MEET A FULL ISO 9001 CERTIFIED FACTORY MANUFACTURED TO ISO 9001
- RECOMMENDED FOR APPLICATIONS WHERE DURABILITY, STABILITY AND PRECISION ARE REQUIRED

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7514™	+0.000 -0.005 -0.013	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	0.025 1.59	7500 19.05	1.306 33.17

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	A (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.138 3.45	0.042 1.07	2.1563 54.77	0.035 0.89	9970 13217	1950 6008	0.36 0.16	1.125 28.58	1.750 44.45	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)  
 ② Tolerance for 7514™ and larger is +0.000/-0.005 (+.000/-0.015)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of FBC NICE® Bearings.

## PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473301
Binnendiameter	22.23 mm
Buitendiameter	50.8 mm
Dikte	15.88 mm
Gewicht	160 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE