

Kogellager enkele rij 400-47V-NICE - 400-47V-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/400-47v-nice>



- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	47V	1.250 31.75 +0.000/-0.005	2.625 66.68 +0.035/0.000 +0.000/-0.005	0.687 17.45 +0.010/-0.010 +0.000/-0.005	0.687 17.45 Reference	23	1/4

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.75 0.34	1020 4539	710 3160	490 2181	395 1758	275 1224	193 869

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560175
Binnendiameter	31.75 mm
Buitendiameter	66.68 mm
Dikte	17.45 mm
Gewicht	340 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE